



EcoCove Technical Data Sheet

1. PRODUCT PROFILE

General Description

EcoCove Systems come in 4", 6" and 1.5" - 45-degree molding pieces. They are pre-formed, plant based urethane molding made for use with any liquid resinous or troweled on flooring systems. After area is coated, EcoCove provides for a smooth, seamless, and integral floor-to-wall junction that is water-proof and chemical-proof.

Common Use

EcoCove is compatible with most epoxy, polyurethane, polyureas and cementitious overlays. It can be used for both utility and decorative purposes and used in a multitude of facilities such as commercial, institutional, industrial kitchen and bathrooms, food processing and storage, offices, hospitals and veterinarian facilities.

Composition

EcoCove is derived from a Zero-VOC, 100% solids, 2-component Polyurethane Elastomer with 46% of product based on renewable, plant based material.

Shelf Life

None

2. PHYSICAL CHARACTERISTICS (see diagrams at end)

4" Tall Radius Cove base

- Actual height: 4"
- Cove radius: 2"
- Base portion thickness: 1/4"
- Length: 8' (may be shipped in 4' sections)
- Total distance from wall: 1 1/4"

6" Tall Radius Cove base

- Actual height: 6"
- Cove radius: 2"
- Base portion thickness: 1/4"
- Length: 8' (may be shipped in 4' sections)
- Total distance from wall: 1 1/4"

"45-degree" Tall Radius Cove base

- Actual height: 2"
- Cove radius: 45-degree
- Base portion thickness: 2 $\frac{3}{4}$ "
- Length: 8' (may be shipped in 4' sections)
- Total distance from wall: 2"

3. RECOMMENDED ADHESIVE

EcoCove can be adhered to any substrate with a two-part epoxy of urethane material that is thin and can be applied by a trowel. A recommended adhesive is the DFL-900 2-C Thixotropic Polyurethane Adhesive, manufactured by Gold Medal Construction Corporation, Lehigh Acres, FL, (239) 303-7380. EcoCove system is pliable and can be notched to even fit around circular columns.

4. PRODUCT WARRANTY

Gold Medal Construction Corporation (GMCC) warrants only that EcoCove conforms to GMCC's custom quality standards. If any EcoCove product is defective SRE shall, at its own discretion, replace the product or refund at the original purchase price. That replacement or refund should be the sole remedy.

